TV and 41 dB $\mu$  V/m coverage contour for DTV stations) will be achieved. Directions for calculating powers, heights, and reduction curves are listed in \$90.309 of this chapter for land mobile stations. Directions for calculating coverage contours are listed in \$§73.683 through 73.685 of this chapter for TV stations and in \$73.625 of this chapter for DTV stations.

- (ii) Control, fixed, and mobile stations (including portables) that operate in the 776–777 MHz and 792–794 MHz bands and control and mobile stations (including portables) that operate in the 698–746 MHz, 747–762 MHz and 777–792 MHz bands are limited in height and power and therefore shall afford protection to co-channel and adjacent channel TV/DTV stations in the following manner:
- (A) For control, fixed, and mobile stations (including portables) that operate in the 776-777 MHz and 792-794 MHz bands and control and mobile stations (including portables) that operate in the 747-762 MHz and 777-792 MHz band, co-channel protection shall be afforded in accordance with the values specified in Table D (co-channel frequencies based on 40 dB protection for TV stations and 17 dB for DTV stations) in §90.309 of this chapter.
- (B) For control and mobile stations (including portables) that operate in the 698–746 MHz band, co-channel protection shall be afforded to TV stations in accordance with the values specified in Table D (co-channel frequencies based on 40 dB protection) and to DTV stations by providing 23 dB protection to such stations' equivalent Grade B contour (41 dB $\mu$ V/m).
- (C) For control, fixed, and mobile stations (including portables) that operate in the 776–777 MHz and 792–794 MHz bands and control and mobile stations (including portables) that operate in the 698–746 MHz, 747–762 MHz, and 777–792 MHz band, adjacent channel protection shall be afforded by providing a minimum distance of 8 kilometers (5 miles) from all adjacent channel TV/DTV station hypothetical or equivalent Grade B contours (adjacent channel frequencies based on 0 dB protection for TV stations and –23 dB for DTV stations).

(D) Since control, fixed, and mobile stations may affect different TV/DTV stations than the associated base or fixed station, particular care must be taken by applicants/licensees to ensure that all appropriate TV/DTV stations are considered (e.g., a base station may be operating within TV Channel 62 and the mobiles within TV Channel 67, in which case TV Channels 61, 62, 63, 66, 67 and 68 must be protected). Control, fixed, and mobile stations shall keep a minimum distance of 96.5 kilometers (60 miles) from all adjacent channel TV/DTV stations. Since mobiles and portables are able to move and communicate with each other, licensees must determine the areas where the mobiles can and cannot roam in order to protect the TV/DTV stations.

Note to \$27.60: The 88.5 km (55 mi) Grade B service contour (64 dB $\mu$ V/m) is based on a hypothetical TV station operating at an effective radiated power of one megawatt, a transmitting antenna height above average terrain of 610 meters (2000 feet) and the Commission's R-6602 F (50,50) curves. See §73.699 of this chapter. Maximum facilities for TV stations operating in the UHF band are 5 megawatts effective radiated power at an antenna HAAT of 610 meters (2,000 feet). See §73.614 of this chapter. The equivalent contour for DTV stations is based on a 41 dB $\mu$ V/m signal strength and the distance to the F (50,90) curve. See §73.625 of this chapter.

[65 FR 3148, Jan. 20, 2000, as amended at 65 FR 17605, Apr. 4, 2000; 65 FR 42883, July 12, 2000; 67 FR 5511, Feb. 6, 2002]

#### §§ 27.61-27.62 [Reserved]

# § 27.63 Disturbance of AM broadcast station antenna patterns.

AWS and WCS licensees that construct or modify towers in the immediate vicinity of AM broadcast stations are responsible for measures necessary to correct disturbance of the AM station antenna pattern which causes operation outside of the radiation parameters specified by the FCC for the AM station, if the disturbance occurred as a result of such construction or modification.

(a) Non-directional AM stations. If tower construction or modification is planned within 1 kilometer (0.6 mile) of a non-directional AM broadcast station tower, the AWS or WCS licensee must notify the licensee of the AM broadcast

## § 27.64

station in advance of the planned construction or modification. Measurements must be made to determine whether the construction or modification would affect the AM station antenna pattern. The AWS or WCS licensee is responsible for the installation and continued maintenance of any detuning apparatus necessary to restore proper non-directional performance of the AM station tower.

(b) Directional AM stations. If tower construction or modification planned within 3 kilometers (1.9 miles) of a directional AM broadcast station array, the AWS or WCS licensee must notify the licensee of the AM broadcast station in advance of the planned construction or modification. Measurements must be made to determine whether the construction or modification would affect the AM station antenna pattern. The AWS or WCS licensee is responsible for the installation and continued maintenance of any detuning apparatus necessary to restore proper performance of the AM station array.

[69 FR 5715, Feb. 6, 2004]

# § 27.64 Protection from interference.

Wireless Communications Service (WCS) stations operating in full accordance with applicable FCC rules and the terms and conditions of their authorizations are normally considered to be non-interfering. If the FCC determines, however, that interference which significantly interrupts or degrades a radio service is being caused, it may, after notice and an opportunity for a hearing, require modifications to any WCS station as necessary to eliminate such interference.

- (a) Failure to operate as authorized. Any licensee causing interference to the service of other stations by failing to operate its station in full accordance with its authorization and applicable FCC rules shall discontinue all transmissions, except those necessary for the immediate safety of life or property, until it can bring its station into full compliance with the authorization and rules.
- (b) Intermodulation interference. Licensees should attempt to resolve such interference by technical means.

- (c) Situations in which no protection is afforded. Except as provided elsewhere in this part, no protection from interference is afforded in the following situations:
- (1) Interference to base receivers from base or fixed transmitters. Licensees should attempt to resolve such interference by technical means or operating arrangements.
- (2) Interference to mobile receivers from mobile transmitters. No protection is provided against mobile-to-mobile interference.
- (3) Interference to base receivers from mobile transmitters. No protection is provided against mobile-to-base interference.
- (4) Interference to fixed stations. Licensees should attempt to resolve such interference by technical means or operating arrangements.
- (5) Anomalous or infrequent propagation modes. No protection is provided against interference caused by tropospheric and ionospheric propagation of signals.

### §27.66 Discontinuance, reduction, or impairment of service.

- (a) Involuntary act. If the service provided by a fixed common carrier licensee, or a fixed common carrier operating on spectrum licensed to a Guard Band Manager, is involuntarily discontinued, reduced, or impaired for a period exceeding 48 hours, the licensee must promptly notify the Commission, in writing, as to the reasons for discontinuance, reduction, or impairment of service, including a statement when normal service is to be resumed. When normal service is resumed, the licensee must promptly notify the Commission.
- (b) Voluntary act by common carrier. If a fixed common carrier licensee, or a fixed common carrier operating on spectrum licensed to a Guard Band Manager, voluntarily discontinues, reduces, or impairs service to a community or part of a community, it must obtain prior authorization as provided under §63.71 of this chapter. An application will be granted within 31 days after filing if no objections have been

received.

(c) Voluntary act by non-common carrier. If a fixed non-common carrier licensee, or a fixed non-common carrier